



Agilent 1260 Infinity Standard Autosampler

Features, Specifications and Ordering Details



Reliability and Ease of Use

The Agilent 1260 Infinity Standard Autosampler is designed for the reliability, safety, and ease-of-use needed in pharmaceutical routine tasks and quality control, as well as for environmental and food analyses. It can be upgraded from non-thermostatted version to thermostatted version by adding the Agilent 1290 Infinity Thermostat.

Features

- Reliable injections from 0.1 μL to 100 μL .
- Easy adaption for injection volumes up to 1500 μL for applications ranging from microbore to semipreparative chromatography.
- Low internal volume of 300 μL for the minimum contribution to a system's total internal volume can be even further reduced using "by-pass" mode.
- Overlapped injections for increased productivity.
- Peltier temperature control from 4 to 40 $^{\circ}\text{C}$ for up to 100 2-mL vials containing thermally labile samples (upgrade from non-thermostatted to thermostatted version possible).



Agilent Technologies

Specifications – Agilent 1260 Infinity Standard Autosampler

Specifications for 1260 Infinity Standard Autosampler Valid with standard 100 µL metering head installed	
Injection range	0.1- 100 µL in 0.1 µL increments Up to 1500 µL with multiple draw (hardware modification required)
Precision	<0.25% RSD from 5-100 µL, <1% from 1-5 µL, variable volume
Sample viscosity range	0.2 - 5 cp
Sample capacity	100 x 2-mL vials in 1 tray 40 x 2-mL vials in 1/2 tray 15 x 6-mL vials in 1/2 tray (Agilent vials only)
Injection cycle time	Typically 50 s depending on draw speed and injection volume
Carryover	Typically < 0.1 %, < 0.05 % with external needle cleaning
Pressure operating range	Up to 600 bar (60 MPa or 8702 psi)

Specifications for 1260 Infinity Standard Autosampler Valid with standard 900 µL metering head installed	
Injection range	0.1 - 900 µL in 0.1 µL increments (recommended 1 µL increments) Up to 1800 µL with multiple draw (hardware modification required)
Precision	Typically < 0.5 % RSD of peak areas from 5 - 2000 µL Typically < 1 % RSD of peak areas from 2000 - 5000 µL Typically < 3 % RSD of peak areas from 1 - 5 µL Variable volume
Sample viscosity range	0.2 - 5 cp
Sample capacity	100 x 2-mL vials in 1 tray 40 x 2-mL vials in 1/2 tray 15 x 6-mL vials in 1/2 tray (Agilent vials only).
Injection cycle time	Typically 50 s depending on draw speed and injection volume
Carryover	Typically < 0.1 %, < 0.05 % with external needle cleaning
Pressure operating range	Up to 200 bar (20 MPa or 2901 psi)

Ordering Details – Agilent 1200 Infinity Series Autosamplers

Description	Product Number
Agilent 1260 Infinity Standard Autosampler Includes 100-vial (2-mL) thermostatted tray, 40-vial (2-mL) tray, 15-vial (6-mL) tray, electrically actuated 600-bar Rheodyne injection valve, and 0.5-m CAN cable.	G1329B
Expanded injection range with 900- μ L syringe, head, loop capillary and injector needle installed and tested in the sampler.	G1329B#020
Multi-draw kit with loop capillaries to inject 500 and 1500 μ L volume	G1329B #021
Agilent 1260 Infinity High Performance Autosampler Includes well-plate tray for two well plate and 10 x 2 mL vials, 2 x 54 (2 mL) vial plate, 600-bar Rheodyne injection valve, and 0.5-m CAN cable.	G1367E
Multi-draw kit with loop capillaries to inject 500 and 1500- μ L volume	G1367E#021
40 μL injection kit for RRLC. Includes loop and analytical head.	G1367E#040
Agilent 1260 Infinity High Performance Micro Autosampler Includes micro autosampler with well-plate tray, 2 x 54 (2 mL) vial plate, electrically actuated Rheodyne micro injection valve, and 0.5 m CAN cable.	G1377A
Agilent 1260 Infinity Preparative Autosampler Includes 100-vial (2-mL) thermostatted tray, 15 x 6 mL half tray (2x), MBB Rheodyne injection valve and 0.5 m CAN cable.	G2260A
Agilent 1260 Infinity Dual Loop Autosampler Includes dual loop autosampler with two loops, tray for two well/vial-plates and 10 x 2 ml vials, Rheodyne injection valve.	G2258A
Agilent 1290 Infinity Autosampler Includes well-plate tray for two well plate and 10 x 2 mL vials, 2 x 54 (2 mL) vial plate, 1200-bar Rheodyne injection valve, and 0.5-m CAN cable.	G4226A
Agilent 1290 Series Thermostat Includes Peltier device to control the temperature of the Agilent 1200 Infinity Series autosamplers, fraction collectors and spotters.	G1330B
Agilent 1260 Infinity Manual Injector Includes 600-bar Rheodyne manual injection valve, 20 μ L sample loop and mounting stand.	G1328C

www.agilent.com/chem/1200

© Agilent Technologies, Inc., 2010
Published in USA, July 1, 2010
Publication Number 5990-6120EN



Agilent Technologies